

CBB Type Volume Distributor



◆ Features

1. CBB type volume distributor can deliver a precisely metered quantity of oil to each lubrication point.
2. CBB needs to work with a pressure-relief type oil lubricator and discharges oil during the operation time of the lubricator.

◆ Dimensional Data & Technical Data

Model	Outlet Num.	Inlet Bore	Outlet Bore	A (mm)	B (mm)	C (mm)	D (mm)	Discharge Volume/Stroke (Volume Marking)	Operating Pressure Range	Suitable Viscosity	N.W (g)
CBB-1	1	Outer Thread M10xP1.0	Ø4 (M8xP1.0)	Ø15	-	-	75	0.1cc (1) 0.2cc (2)	8-30 kgf/cm ²	Oil 32-90 cSt@40°C	79
CBB-2	2	Ø6 (M10xP1.0)		53	37	17	80	0.3cc (3)			178
CBB-3	3			70	54	34	80	0.4cc (4)			250
CBB-5	5			104	88	68	80	0.5cc (5)			410

◆ Order Code

CBB — 5 — A — 1 — 1 — 1 — 1 — 1 — A — A

Left Side Right Side

Code	Outlet Number
1	1
2	2
3	3
5	5

Code	Outlet Adapter Type
A	Compression Bushing & Sleeve

Code	Discharge Volume
0	Plugged
1	0.1cc
2	0.2cc
3	0.3cc
4	0.4cc
5	0.5cc

Code	Inlet Fittings
A	Ø6 Compression Bushing & Sleeve
G	Closure Plug
X	Without Fittings
S	Special Request

※ Except for CBB-1, others all need to provide the order code for inlet fittings.