

HV-201 Air Operated Oil Filler



◆ Features

1. HV-201 are without oil tanks that can work with any oil tank size.
2. HV-201 is that a five-gallon oil tank can place on top of it.
3. It is suitable for various engine oil, lubricants, and gear oil.
4. Oil filling and extracting are driven by a pneumatic motor pump. No contact between the oil and the air prevents the oil from being emulsified.
5. The oil refilling gun or the air pressure can control the speed of filling oil. The oil refilling gun is a standard accessory.
6. It can add a digital flow meter to measure the volume of the refilled oil as optional.

◆ Specification

Model	Rack	Capacity (L)	Dimensions (mm)	Filling Method	Power	Operation Pressure	N.W.	G.W.
HV-201	O	20	360x390x790	Air Pressure	AP-35	5~7 kgf/cm ²	10 kg	11.0 kg

Air Operated Grease Filler



◆ Features

1. High-Grade Steel Construction: Rugged, durable build for long service life.
2. 5-Gallon Capacity: Inner diameter 322mm, depth 440mm; fits standard 5-gallon grease buckets directly.
3. Dual-Circulation Pump: Separates compressed air from grease to reduce contamination and maintain grease quality.
4. Easy Mobility: Four-wheel ring base plus ergonomic handle for smooth transport.
5. Follower Plate Included: Improves priming efficiency and ensures reliable flow in freezing conditions.
6. Versatile compatibility with NLGI 000 to No. 2 grease, suitable for a wide range of industrial lubrication applications.

◆ Specification

Model	Capacity	Air Input Pressure	Pressure Ratio	Grease Output pressure	Discharge Volume	Hose Length	Viscosity	N.W.	G.W.
CKMG-55	20	4~9 kgf/cm ²	45:1	180~405 kgf/cm ²	23.3 g/sec	10 meters	NLGI 000~2	15.75 kg	18.15 kg